

## SECTION 1- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: THERMOTEK™ BASE COAT  
 Product use: Elastomeric base coat for acrylic roofing systems.  
 Chemical Family: Mix of acrylic polymers, pigments, and fillers.  
 Manufacturer Name: Pinturas Termicas del Norte S.A. de C.V.  
 Address: Carretera Monterrey –Monclova km. 19.5  
 City: Abasolo State: Nuevo Leon, México Zip Code: 65650  
 Emergency Telephone: 1 52 (83) 5000 3000



## SECTION 2- COMPOSITION AND INFORMATION ON INGREDIENTS

COMPONENTS	CAS No.	% BY WT
OXIMINO SILANE	22984-54-9	1 - 5
POLYDIMETHYLSILOXANE	70131-67-8	45 - 55

## SECTION 3- HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW:

Appearance, white moderately thick liquid.  
 WARNING! Harmful if swallowed. May cause eye and skin irritation.

<b>HMIS Rating:</b>	<b>HEALTH - 1</b>	<b>FLAMMABILITY - 1</b>	<b>REACTIVITY - 0</b>
<b>NFPA Rating:</b>	<b>HEALTH - 1</b>	<b>FLAMMABILITY - 1</b>	<b>REACTIVITY - 0</b>

### POTENTIAL HEALTH EFFECTS:

Skin	May cause irritation and allergic reaction.
Eyes	May cause irritation and damage.
Inhalation	May cause irritation in the respiratory tract.
Ingestion	May cause stomachache.

## SECTION 4- FIRST-AID MEASURES

Eye Contact:	Flush with large amounts of potable water. Get medical attention.
Skin Contact:	Remove contaminated clothes. Wash with mild soap and water. Get medical attention.
Ingestion:	Do not induce vomiting, if victim is conscious give 1-3 glasses of drinking water. Get medical attention immediately.
Inhalation:	Remove the person from the contaminated area to fresh air. Give artificial respiration if necessary.

## SECTION 5- FIRE AND EXPLOSION HAZARDS

Flammability (explain conditions)	N. AP.
Flash Point (°F) & Method of determination	N. AV.
Upper Flammability (% by volume)	N. AP.
Lower Flammability (% by volume)	N. AP.
Auto-Ignition Temp (°F)	N. AP.
Explosion Data	N. AP.
Hazardous Combustion Products	Silicone Dioxide, Carbon Monoxide and Dioxide, Formaldehyde
Sensitivity to Static Discharge	N. AP.

## SECTION 6- ACCIDENTAL RELEASE MEASURES

### LEAK OR SPILL PROCEDURE:

Avoid breathing vapors, ventilate area, remove with inert absorbent, floor may be slippery, use caution to avoid falling.

### WASTE DISPOSAL

Dispose of in accordance with Local, State and Federal Regulations. Incinerate in approved facility, do not incinerate in closed container.

## SECTION 7-HANDLING AND STORAGE

### STORAGE REQUIREMENTS:

Do not store above 77 °F (25°C). Store in close containers. Open containers should be blanketed with dry nitrogen before resealing.

### SPECIAL HANDLING INFORMATION

Heat, sparks and open flame must be avoided.

